

FILM RELEASE LINERS

5000 SERIES

THE 5000 SERIES of film release liners are based on tincatalyzed silicone release coatings designed for easy and controlled releases for multiple-film bases.

Easy Release (≤ 30 grams per 2"peel)

- **5014:** For thermoformable films.
- **5018:** Our most popular, suitable for most films. Excellent optical properties.

Moderate Release (30 - 100 grams per 2" peel)

• **5029:** Moderate release used with super clear polyester.

Tight Release (>100 grams per 2" peel)

- 5032: Tight release for use on polyester.
- 5035: Tight release for use on polyester.

Custom Release

Custom formulations are available. Contact your sales representative for more information.

*Previously known as NORFILM® 5000 SERIES

FEATURES AND BENEFITS

- Easy, smooth release
- Compatible with most adhesives
- Excellent clarity and optics
- Multiple film bases and gauges
- Thermoformable formulations available



Limitations

- Limited availability on heat-sensitive films
- Not ideal for solvent-sensitive films
- Poor abrasion resistance
- Longer process time and lead time
- Not available for coated two side (C2S) products
- Not FDA-compliant





CORETECH FILM SELECTION GUIDE

Film	Gauge	Market	Applications	Key Properties
Polyester (PET)	92 - 1400	Label	Roll Label, Overlaminates, Beverage, Pharmaceutical, Toiletries, Health & Beauty	 High Tensile and Tear Resistance Excellent Smoothness High Clarity Gauge Control Temperature Resistance Recyclable Back Side Printable Mechanically Stable Spliceable
		Decal Graphic	Transfer Lettering, Window Graphics	
		Industrial	Solar, Gaskets, Nameplate, Automotive, Construction, Composites, Free Adhesives	
		Tape	One/Two Side, Transfer	
		Medical	Transdermal, Hydrogels, Wound Care, EKG, Hygiene	
Polystyrene (PS)	750 - 1000	Medical	Hydrogels, Wound Care, EKG	ThermoformableGood StiffnessBack Side Printable
		Label	Piggyback	
Polyvinyl Chloride (PVC)	800 - 1000	Medical	Transdermal, Hydrogels, EKG	Thermoformable
Polyethylene (PE)	100 - 2300	Tape	One/Two Side, Transfer	Tear ResistanceConformableHigh Yield
		Medical	Wound Care, Hygiene	
		Industrial	Construction Gasket, Automotive	

The values presented are typical values and should not be used for specification purposes.

Contact your CoreTech Performance Film Solutions representative for more information.

CONTACT CORETECH PERFORMANCE FILM SOLUTIONS

Americas

Saint-Gobain Performance Film Solutions 717 Plantation Street Worcester, MA 01605 Tel: (508) 852-3072 Fax: (508) 852-3759

www.coretechfilms.com

IMPORTANT: The values presented are typical values and should not be used for specification purposes. Contact your representative for more information. It is the user's responsibility to ensure the suitability and safety of CoreTech products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. CoreTech assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated by purchaser and/or user.

WARRANTY: We warranty specifications at delivery and honor claims for such breach of warranty for six (6) months after delivery. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks; if any, including the risk of injury, loss or damage, whether direct or consequential arising out of the use, misuse or inability to use this product(s). CORETECH DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

 $@\ 2024\ Saint-Gobain\ High\ Performance\ Solutions\ and/or\ its\ affiliates\ |\ CoreTech\ is\ a\ service\ mark\ of\ Saint-Gobain\ Box{Box}.$

Valid 01/2024 • Supersedes all previous versions

