

ADHESIVE RELEASE LINERS

7732 MODERATE SILICONE RELEASE

7732 Silicone Release Coating was designed with moderate release properties for use as the casting liner for a 2 liner differential construction. 7732 exhibits stable release against highly aggressive acrylic adhesives. This coating exhibits excellent adhesion to a variety of Polyester and Polyolefin film bases. 7732 has a smooth surface and has excellent winding characteristics.

*Previously known as

NORFILM® 7732 UV MODERATE SILICONE RELEASE



- Smooth uniform surface
- Excellent adhesion to base film
- Excellent clarity and optics
- Excellent solvent resistance
- Can be used in coated Both sides product

TYPICAL PROPERTIES

Subsequent Adhesion	86% Minimum	
SG Wet Spread Release	20 – 50 grams/inch	
Tesa 7475 Tape Release	20 – 40 grams/inch	
Solvent Resistance	Excellent	
Coating Warranty	12 Months	

The values presented are typical values and should not be used for specification purposes. Contact your CoreTech Performance Film Solutions representative for more information.



Limitations:

 Cure inhibition by amines or process aids in some films

APPLICATIONS

- Differential Liner
- Tag and Label





CORETECH FILM SELECTION GUIDE

Film	Gauge	Market	Applications	Key Properties
Polyester (PET)	92 - 1400 Industri Tape	Label	Roll Label, Overlaminates, Beverage, Pharmaceutical, Toiletries, Health & Beauty	 High Tensile and Tear Resistance Excellent Smoothness High Clarity Gauge Control Temperature Resistance Recyclable Back Side Printable Mechanically Stable Spliceable
		Decal Graphic	Transfer Lettering, Window Graphics	
		Industrial	Solar, Gaskets, Nameplate, Automotive, Construction, Composites, Free Adhesives	
		Tape	One/Two Side, Transfer	
		Medical	Transdermal, Hydrogels, Wound Care, EKG, Hygiene	
Polystyrene (PS)	Medical 750 - 1000 Label	Medical	Hydrogels, Wound Care, EKG	ThermoformableGood StiffnessBack Side Printable
		Label	Piggyback	
Polyvinyl Chloride (PVC)	800 - 1000	Medical	Transdermal, Hydrogels, EKG	Thermoformable
Polyethylene (PE)	100 - 2300 Me	Tape	One/Two Side, Transfer	Tear ResistanceConformableHigh Yield
		Medical	Wound Care, Hygiene	
		Industrial	Construction Gasket, Automotive	

The values presented are typical values and should not be used for specification purposes.

Contact your CoreTech Performance Film Solutions representative for more information.

CONTACT CORETECH PERFORMANCE FILM SOLUTIONS

Americas

Saint-Gobain Performance Film Solutions 717 Plantation Street Worcester, MA 01605 Tel: (508) 852-3072 Fax: (508) 852-3759

www.coretechfilms.com

IMPORTANT: The values presented are typical values and should not be used for specification purposes. Contact your representative for more information. It is the user's responsibility to ensure the suitability and safety of CoreTech products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. CoreTech assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated by purchaser and/or user.

WARRANTY: We warranty specifications at delivery and honor claims for such breach of warranty for six (6) months after delivery. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks; if any, including the risk of injury, loss or damage, whether direct or consequential arising out of the use, misuse or inability to use this product(s). CORETECH DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

 $@\ 2024\ Saint-Gobain\ High\ Performance\ Solutions\ and/or\ its\ affiliates\ |\ CoreTech\ is\ a\ service\ mark\ of\ Saint-Gobain\ Box{Baint-Gobain\ Box{B$

Valid 01/2024 • Supersedes all previous versions

