

ADHESIVE RELEASE LINERS

8711

MODERATE SILICONE RELEASE

8711 A product designed primarily for use in casting applications, such as Ceramic PVC (Vinyl), and PU (Polyurethane), and various ink systems. 8711 is a UV cured system that has been specially designed for controlled release properties, exhibits excellent optical properties and a smooth uniform surface.

FEATURES AND BENEFITS

- Smooth uniform surface
- Good adhesion to base film
- Excellent clarity and optics
- Excellent solvent resistance
- Excellent winding characteristics

APPLICATIONS

- Ceramic casting (Green tape)
- Other casting applications

TYPICAL PROPERTIES

Subsequent Adhesion	86% Minimum
Test #125 Wet Spread Peel	50 - 70 grams/2 inch
Solvent Resistance	Excellent
Coating Warranty	12 Months

The values presented are typical values and should not be used for specification purposes. Contact your CoreTech Performance Film Solutions representative for more information.



CORETECH FILM SELECTION GUIDE

Film	Gauge	Market	Applications	Key Properties
Polyester (PET)	92 - 1400	Label	Roll Label, Overlaminates, Beverage, Pharmaceutical, Toiletries, Health & Beauty	<ul style="list-style-type: none"> • High Tensile and Tear Resistance
		Decal Graphic	Transfer Lettering, Window Graphics	<ul style="list-style-type: none"> • Excellent Smoothness • High Clarity
		Industrial	Solar, Gaskets, Nameplate, Automotive, Construction, Composites, Free Adhesives	<ul style="list-style-type: none"> • Gauge Control • Temperature Resistance • Recyclable
		Tape	One/Two Side, Transfer	<ul style="list-style-type: none"> • Back Side Printable • Mechanically Stable
		Medical	Transdermal, Hydrogels, Wound Care, EKG, Hygiene	<ul style="list-style-type: none"> • Spliceable
Polystyrene (PS)	750 - 1000	Medical	Hydrogels, Wound Care, EKG	<ul style="list-style-type: none"> • Thermoformable • Good Stiffness
		Label	Piggyback	<ul style="list-style-type: none"> • Back Side Printable
Polyvinyl Chloride (PVC)	800 - 1000	Medical	Transdermal, Hydrogels, EKG	<ul style="list-style-type: none"> • Thermoformable
Polyethylene (PE)	100 - 2300	Tape	One/Two Side, Transfer	<ul style="list-style-type: none"> • Tear Resistance
		Medical	Wound Care, Hygiene	<ul style="list-style-type: none"> • Conformable
		Industrial	Construction Gasket, Automotive	<ul style="list-style-type: none"> • High Yield

The values presented are typical values and should not be used for specification purposes.

Contact your CoreTech Performance Film Solutions representative for more information.

CONTACT CORETECH PERFORMANCE FILM SOLUTIONS



Americas
Saint-Gobain Performance Film Solutions
717 Plantation Street
Worcester, MA 01605
Tel: (508) 852-3072
Fax: (508) 852-3759
www.coretechfilms.com

IMPORTANT: The values presented are typical values and should not be used for specification purposes. Contact your representative for more information. It is the user's responsibility to ensure the suitability and safety of CoreTech products for all intended uses and that the materials to be used comply with all applicable regulatory requirements. CoreTech assumes no responsibility for any product failures that occur due to misuse of the materials it provides arising out of the design, fabrication or application of the products into which the materials are incorporated by purchaser and/or user.

WARRANTY: We warranty specifications at delivery and honor claims for such breach of warranty for six (6) months after delivery. The only obligation under any applicable product warranty will be to replace any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential arising out of the use, misuse or inability to use this product(s). CORETECH DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

© 2024 Saint-Gobain High Performance Solutions and/or its affiliates | CoreTech is a service mark of Saint-Gobain.

Valid 01/2024 • Supersedes all previous versions

CT.PDS.4130UV.NAM.EN.V1